

## Schedule C

- (b) A neighbourhood identification sign must:
  - (i) be a self-supported sign;
  - (ii) not exceed 6 sq. m in sign area;
  - (iii) not exceed 3 m in sign height; and
  - (iv) in accordance with City policy, incorporate the neighbourhood name specified by the relevant plans or bylaw.
- (c) A neighbourhood identification sign may incorporate the logogram of the developer.

### (18) Portable Sign

- (a) Subject to the issuance of a development permit, a portable sign is a permitted use in C1, C2, CC, RC, ICC, and CIS Districts.
- (b) As a discretionary use subject to the issuance of a Development Permit, a portable sign may be located in UR, P, PS and IF districts.
- (c) Portable signs must:
  - (i) not exceed 5 sq. m in sign area;
  - (ii) not exceed 2.5 m in sign height;
  - (iii) be located no less than 1.5 m from any property line; and
  - (iv) maintain a separation distance of 30 m from another portable sign.
- (d) **In C2, RC and CC districts**, portable signs are limited to a maximum of 1 sign for sites with frontages up to 30 m.
- (e) **In C2, RC and CC districts**, portable signs are limited to a maximum of 2 signs per site for sites with frontages greater than 30 m, but in no case is more than 1 sign per business allowed.
- (f) In the ICC district, a portable sign must be separated by a minimum of 400 m from another portable sign.
- (g) A development permit for a portable sign is valid for a maximum of 90 days.

### (19) Projecting Sign

- (a) Subject to the issuance of a development permit, a projecting sign is a permitted use in R4, CC, RC, C1, C2, MC, BW, PS, IF, DCMU, DCNUV, DT and industrial districts.
- (b) A projecting sign must:
  - (i) not exceed 0.5 sq. m in sign area;
  - (ii) be placed so that the distance between the nearest edge of the sign and the building to which it is attached does not exceed 0.35 m;
  - (iii) provide a minimum vertical clearance of 2.5 m from finished grade to the bottom of the sign;
  - (iv) have clearance from any electrical power lines or other utilities and provide for safe pedestrian movement or any other activities or use underneath the projecting sign;
  - (v) except for corner locations, be located at right angles to the building facade;